


Open Source
MANO

OSM#9 Hackfest


Underlay Automation with SDN Assist

Gianpietro Lavado (Whitestack)

Using Virtual Interfaces (VIRTIO)




Using Physical Interfaces (SR-IOV/PASSTHROUGH)




SR-IOV and Passthrough features expose the instance directly to the physical NIC, so **who takes care of the end-to-end connectivity?**

1. OSM orchestrates SR-IOV or Passthrough
→ Proper assignment of I/O physical interfaces to the VM (PFs or VFs = Physical or Virtual Functions)
1. OSM SDN Assist gives the ability to create L2 connections between VFs
 - Interconnecting VMs
 - Attaching external traffic sources



SDN Assist

VXLAN, OpenFlow,
VLAN, etc.
(depends on the SDN
Controller or Manager)



OSM's SDN Assist
feature takes care of
the “underlay”
connectivity **whenever**
it sees VLDs with
SR-IOV or
PASSTHROUGH ports
that need to connect
between each other.


* Supported as of REL7.0.1 → ONOS, Arista, Contrail, Open Daylight and Floodlight

SDN Assist requirements

- The VIM must have been created with a reference to the physnet(s) to use for SR-IOV (typically something like: `--config '{dataplane_physical_net: <name>, microversion: 2.32}'`)
- An compatible SDN Controller of Config Manager must be installed and it must be reachable from OSM.
- For certain plugins (at least the OpenFlow based), an "SDN Port Mapping" file must be prepared to include all the possible PCI ports that can be selected by the VIM, per port.
- The VIM user must have admin privileges or rights to get the PCI information.
- Finally, the VIM and SDNC must be configured properly in OSM.
- More information here:
<https://osm.etsi.org/docs/user-guide/04-vim-setup.html#using-sdn-assist>

Back to our scenario!

In our example, we can configure the S1 data interface, currently using VIRTIO drivers (OVS/VxLAN) to use SR-IOV instead. We can also set the descriptor to request CPU Pinning, memory Huge Pages, and stick the VDUs to a single NUMA node. Today in OSM, all these optimizations are applied automatically when selecting SR-IOV in one of the interfaces, in order to match the packet processing capabilities that the direct connection to the NIC will allow for.



Preparing the environment

1. Create the SDN Controller, replacing XX with your tenant number-

```
osm sdnc-create --name onosXX --type onos_vpls --url http://172.21.248.57:8181 --user karaf --password karaf
```

2. Download the recommended SDN Port Mapping file

```
wget http://osm-download.etsi.org/ftp/osm-7.0-seven/OSM9-hackfest/files/magma_sdn_port_mapping.yaml
```

3. Update your VIM to know about the SDNC and the mapping file

```
osm vim-update etsi-openstackXX --sdn_controller onosXX --sdn_port_mapping magma_sdn_port_mapping.yaml
```


Modifying the S1s to use “SR-IOV”

hackfest_magma-agw-enb_vnfd

eth0 interface of MagmaAGW VDU (Line 96)

```
76     vdu:
77     -   alarm:
78     -     actions:
79     -       alarm:
80     -       - url: https://webhook.site/5706da10-04a0-4ab0-819b-cb524f71a367
81     -       alarm-id: cpu-above-threshold
82     -       operation: GT
83     -       value: 80
84     -       vnf-monitoring-param-ref: agw_cpu_util
85     cloud-init-file: magmaagw_init
86     count: 1
87     description: magma-agw-vdu
88     id: magma-agw-vdu
89     image: magma101_hf9
90     interface:
91     -   internal-connection-point-ref: agw-s1
92     -   name: eth0
93     -   position: 1
94     -   type: INTERNAL
95     -   virtual-interface:
96     -     type: SR-IOV
```

eth1 interface of srsLTE VDU (Line 144)


```
128     -   cloud-init-file: srslte_init
129     -   count: 1
130     -   description: srsLTE-vdu
131     -   id: srsLTE-vdu
132     -   image: srsLTEzmqrF_hf9
133     -   interface:
134     -     -   external-connection-point-ref: srsLTE-mgmt
135     -     -   mgmt-interface: true
136     -     -   name: eth0
137     -     -   type: EXTERNAL
138     -     -   virtual-interface:
139     -     -     type: PARAVIRT
140     -     -   internal-connection-point-ref: srsLTE-s1
141     -     -   name: eth1
142     -     -   type: INTERNAL
143     -     -   virtual-interface:
144     -     -     type: SR-IOV
```


Launch your NSI!

1. Use the scripts already in place

```
./launch_nsi.sh
```

2. Check the connectivity between VDUs and explore the network assigned in OpenStack
3. Optionally, visit the ONOS Controller UI at <http://172.21.248.57:8181/onos/ui/login.html> to check topology and flows (which you will see only if assigned different ports)





Open Source MANO

Find us at:

osm.etsi.org
osm.etsi.org/wikipub